



GATOR SEAL NATURAL LOOK FOR CONCRETE OR CLAY PAVERS,
RETAINING WALLS, MASONRY AND NATURAL STONES
TDS Revision Date (dd/mm/yyyy): 04/04/2012



Technical Data Sheet

UPDATE:

April 04, 2012

Make sure you have an updated data sheet on hand.

Canada and U.S. dial **1-855-212-1611** or (450) 624-1611

DESCRIPTION:

GATOR SEAL NATURAL LOOK is made from fluorochemical polymers. This sealer penetrates deep into the concrete or clay pavers, retaining walls, masonry and natural stones, thus reducing the oil and dirt penetration, as well as protecting them from de-icing salt.

-WATER-BASED

-NATURAL FINISH

FEATURES:

- Clear, transparent, invisible protection
- Non film forming
- Non slip formula
- Easier to clean & maintain
- Applicable on damp surfaces

HELPS RESIST:

- Corrosion from de-icing salt
- Ultraviolet rays effects
- Motor oil & grease stains
- Stains up to 10 years

COVERAGE:

- 3.78 l (1 u.s. gal.) covers 16m² (175 ft²)
- 18.9 l (5 u.s. gal.) covers 80m² (875 ft²)

FOR USE ON:

Concrete or clay pavers, retaining walls, masonry and natural stones.

APPLICATION INSTRUCTIONS:

Method of application of GATOR SEAL NATURAL LOOK for **PAVERS & NATURAL STONES :**

1. Remove all contaminated jointing material and replace with GATOR POLYMERIC SAND. Follow the instructions on the back of the bags for proper polymeric sand installation.
2. Wait at least 48 hours at a minimum temperature of 60°F (15°C) and no rain for the GATOR POLYMERIC SAND to properly harden.
3. Clean off any stains with GATOR CLEAN products. Then use the GATOR CLEAN EFFLORESCENCE CLEANER to remove the efflorescence trapped or GATOR CLEAN SHAMPOO if we have no efflorescence in the concrete paver or natural stone pores as well as thoroughly clean the surface for proper sealer adhesion.
4. Apply 1 coat of GATOR SEAL using a foam roller or sprayer on a dry or damp paver surface.
5. Let the sealer dry 24 hours for vehicular application before using the sealed area.

Method of application of GATOR SEAL NATURAL LOOK for **RETAINING WALLS & MASONRY :**

1. Use the GATOR CLEAN EFFLORESCENCE CLEANER to remove the efflorescence trapped or GATOR CLEAN SHAMPOO if we have no efflorescence in the concrete paver or natural stone pores. It also thoroughly cleans the surface to ensure a proper sealer adhesion.
2. Apply only 1 coat of GATOR SEAL using a foam roller or sprayer.
3. Let the sealer dry.

IMPORTANT Wear protective gloves, eye protection and respiratory protection.

Alliance Designer Products Inc.



GATOR SEAL NATURAL LOOK FOR CONCRETE OR CLAY PAVERS, RETAINING WALLS, MASONRY AND NATURAL STONES
TDS Revision Date (dd/mm/yyyy): 04/04/2012



GATOR STONE GUARD, is made from a high tech formulation, provides an invisible protection that acts as a shield. This breathable long lasting sealer deeply penetrates into the stone pores and resists stains for up to 10 years.

CLAY PAVERS: If using polymeric sand as jointing material, we recommend a test area. Some clay pavers are more porous and retain humidity, this might cause the polymers to react on the damp surface and cause a haze.
*Please store container at above 0°C / 32°F.

LIMITED WARRANTY:


10 YEAR LIMITED WARRANTY FOR RESIDENTIAL PURPOSES ONLY

Please note that this limited warranty applies only when the product is used for residential purposes exclusively (home owners or contractors using the product for single or multi-unit dwellings that are exclusively for residential use). The manufacturer cannot guarantee results as it has no control over surface and sub-surface preparation and product application. However, for a period of 10 years from purchase, *Alliance Designer Products inc.* agrees that, if the product is proven to be defective, and on the condition that it was installed pursuant to the method of application of surface and sub-surface preparation described in the *installation guide, then *Alliance Designer Products inc.* agrees to refund the purchase price. Proof of purchase is required for any claim. The parties agree that the refund of the purchase price as stated is the only obligation of *Alliance Designer Products inc.* In all events, *Alliance Designer Products inc.* shall not be liable for any other damages or costs (including removal or reinstallation of sand or pavers) whatsoever, direct or consequential, to the extent permitted by law, *Alliance Designer Products inc.* excludes any implied warranty of quality merchantability or fitness for purpose.

1 YEAR LIMITED WARRANTY

Please note that when the product is used for other purposes (mixed-use, commercial, institutional or other), the above terms apply except that the applicable period is reduced to 1 year from the purchase.

DANGEROUS FUMES FORM WHEN MIXED WITH OTHER CHEMICALS. Do not get in eyes or on skin or clothing. Keep out of reach of children. First aid treatment: If swallowed, call Poison Control centre or doctor immediately. Do not induce vomiting. If in eyes rinse well with water for at least 15 minutes. If on skin, rinse well with water.



SEE INSTALLATION VIDEO
ON ALLIANCEGATOR.COM

Alliance Designer Products Inc.