



GATOR SEAL WET LOOK  
FOR CONCRETE PAVERS & NATURAL STONES  
TDS Revision Date (dd/mm/yyyy): 04/04/2012



## Technical Data Sheet

### UPDATE:

April 04, 2012  
Make sure you have an updated data sheet on hand.  
Canada and U.S. dial **1-855-847-7767** or (450) 624-1611

### DESCRIPTION:

**GATOR SEAL WET LOOK** is made from acrylic based polymers. **GATOR SEAL WET LOOK** penetrates deep into the concrete paver and natural stone pores, thus reducing the oil and dirt penetration, as well as protecting them from de-icing salt.

-HIGH GLOSS FINISH  
-SOLVENT-BASED

### FEATURES:

- Easier to clean and maintain
- Non slip formula

### HELPS RESIST:

- Corrosion from de-icing salt
- Ultraviolet rays effects
- Motor oil & grease stains

### COVERAGE:

- 3.78 l (1 u.s. gal.) covers 16m<sup>2</sup> (175 ft<sup>2</sup>)
- 18.9 l (5 u.s. gal.) covers 80m<sup>2</sup> (875 ft<sup>2</sup>)

### FOR USE ON:

Concrete pavers and natural stones.

### PLEASE NOTE:

1. Pavers should only be sealed 60 days after their installation date.
2. Pavers and jointing sand **MUST** be 100% dry.
3. Temperature should be between 60°F / 15°C and 85°F / 30°C when sealer is applied.
4. Paver and stone surface must be cool to the touch when sealer is applied.
5. First clean pavers with GATOR CLEAN products. Remove all oil, grease and rust stains.
6. Use GATOR CLEAN EFFLORESCENCE CLEANER to remove any trapped efflorescence in the paver or GATOR SHAMPOO if there is no efflorescence. It also thoroughly cleans the surface to ensure a proper sealer adhesion. Let the pavers or stones dry before any sealer application.
7. Just use 1 layer of sealer because 2 layers and more might trap moisture and lead to white spots on the concrete surface.
8. When using **GATOR SEAL WET LOOK** assure yourself at least 48 hours of dry conditions prior to applying the sealer. If temperature is above 60°F / 15°C, the surface should dry within hours
9. 3.78 L (1 gallon) of product covers an area of 16 m<sup>2</sup> (175 ft<sup>2</sup>), 18.9 L (5 gallons) covers 80 m<sup>2</sup> (875 ft<sup>2</sup>).

### APPLICATION INSTRUCTIONS:

1. Remove all the stains from the pavers, using GATOR CLEAN products.
2. Remove all contaminated jointing material and replace with GATOR POLYMERIC SAND. Follow the instructions on the back of the bags for proper sand installation.
3. Wait at least 48 hours at a minimum temperature of 60°F / 15°C and no rain for the GATOR POLYMERIC SAND to properly harden.
4. Use the GATOR CLEAN EFFLORESCENCE CLEANER to remove the efflorescence trapped or GATOR CLEAN SHAMPOO if we have no efflorescence in the concrete paver or natural stone pores. It also thoroughly cleans the surface to ensure a proper sealer adhesion.

*Alliance Designer Products Inc.*



GATOR SEAL WET LOOK  
FOR CONCRETE PAVERS & NATURAL STONES  
TDS Revision Date (dd/mm/yyyy): 04/04/2012



## APPLICATION INSTRUCTIONS: (CONT.)

5. Wait at least 48 hours at a minimum temperature of 60°F / 15°C and no rain so the sand and paver surface are dry.
6. Apply coat of **GATOR SEAL WET LOOK** using a sprayer and or roller.
7. Let the sealer dry for 24 hours before using the sealed area.

## LIMITED WARRANTY:

*Alliance Designer Products inc.* cannot guarantee results as it has no control over surface preparation and product application. If this product is proven to be defective, on the condition that it was applied pursuant to the required method of application and surface preparation, the sole obligation of *Alliance Designer Products inc.* is to refund the purchase price. Proof of purchase is required for any claim. *Alliance Designer Products inc.* shall not be liable for any other damages whatsoever, direct or consequential. To the extent permitted by law, *Alliance Designer Products inc.* excludes any implied warranty of quality, merchantability or fitness for purpose.

\*Please store container at above 0°C / 32°F.


CONTENTS HARMFUL. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. MAY IRRITATE SKIN. FUMES MAY CATCH FIRE. Do not mix with other household chemicals. Do not swallow. Do not breathe fumes. Do not get on skin or clothing. Do not smoke. Keep out of reach of children. Wear a mask. Use only in a well ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor.

## FIRST AID TREATMENT:

Contains Xylenes. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If on skin, rinse well with water.



**DANGER**  
POISON IRRITANT FLAMMABLE



SEE INSTALLATION VIDEO  
ON ALLIANCEGATOR.COM

*Alliance Designer Products Inc.*