



GATOR ROCK BOND - LIQUID BINDER AGENT KEEPS STONES IN PLACE

TDS Revision Date (dd/mm/yyyy): 12/04/2013



Technical Data Sheet

UPDATE: April 12, 2013

Make sure you have an updated data sheet on hand. Canada and U.S. dial **1-855-847-7767** or (450) 624-1611

DESCRIPTION: Mixed GATOR ROCK BOND with 100% washed and dried riverstone creates a durable permeable and

decorative surface. Great for garden pathways where erosion and drainage is a concern.

<u>IDEAL FOR:</u> • Banding, edging and trimming

PathwaysWalkways

• Tree wells

FEATURES: • Porous & permeable

• Keeps stones in place

• Reduce maintenance& clean up

• Durable in extreme conditions

High elongationShock absorption

• Easy to apply and easy to repair

• Superb U.V. and weathering resistance

• Solvent free

INSTALLATION INSTRUCTIONS:

TYPES OF ROCK THAT CAN BE USED WITH GATOR ROCK BOND:

GRANITE - LIMESTONE - MARBLE (1/8" to 3/4") these rocks have to be clean, free of dust &100% dry.

METHOD of application of **GATOR ROCK BOND**:

- 1. Prepare a solid base by densely compacting 4" (10 cm) of crushed stones.
- 2. Mix in a ratio of one container (1 US gal.) of **GATOR ROCK BOND** with (265 lbs) of the above mentioned stones for 4 minutes.

 Mix products automatically with a masonry mixer or you can manually mix on a sheet of plywood or in a wheel barrow.
- 3. Trowel the mixed riverstone on the surface desired, within 20 minutes after mixing.



PLEASE NOTE:

- For pedestrian use only.
- Works above 60°F (16°C).
- Allow 24 hours to dry without rain.

COVERAGE:

1 US gal mixed with 265 lbs of dry stonewill cover 80 sq. ft. (7.4 sq. m.). The size of the stone are to be between 1/8" & 3/4" for a minimum 3/4" surface thickness.

STORAGE:

Store in a cool, dry, well ventilated area. Store in upright position. Store at above freezing temperature 32°F (0°C). Shelf life is 1 year in original unopened container.

WARNING!

Refer to material safety data sheet for further information. Toxic if swallowed. Avoid ingestion or eye contact. Avoid contact with strong alkalines or acids.





GATOR ROCK BOND - LIQUID BINDER AGENT KEEPS STONES IN PLACE

TDS Revision Date (dd/mm/yyyy): 12/04/2013



FIRST AID:

INGESTION:

Call physician or Poison control centre immediately. Do not induce vomiting unless directed to do so by medical personnel. **Eye Contact:** Flush contaminated area with water for 15 minutes. Consult a physician if necessary.

WARRANTY:

ALLIANCE DESIGNER PRODUCTS INC. cannot guarantee results as it has no control over surface and sub-surface preparation and product application. ALLIANCE DESIGNER PRODUCTS INC. agrees that, if the product is proven to be defective, and on the condition that it was installed pursuant to the method of application of surface and sub-surface preparation described above, then ALLIANCE DESIGNER PRODUCTS INC. agrees to refund the purchase price. Proof of purchase is required for any claim. EXCLUSION OF RESPONSIBILITY THE PARTIES AGREE THAT REFUND OF THE PURCHASE PRICE AS STATED IS THE ONLY OBLIGATION OF ALLIANCE DESIGNER PRODUCTS INC., SHALL NOT BE LIABLE FOR ANY OTHER DAMAGES OR COSTS, DIRECT OR CONSEQUENTIAL. TO THE EXTENT PERMITTED BY LAW, ALLIANCE DESIGNER PRODUCTS INC., EXCLUDES ANY IMPLIED WARRANTY OF QUALITY, MERCHANTABILITY OR FITNESS FOR PURPOSE.