


Mezzo singolo

INTONACO SINGLE COMPACT FOLDING FOR SOLID WALLS



STANDARD

misure in mm - sizes in mm

L x H	Z	HT	P	ST	PF	LP x HP
600(300x2) x 2000/2100	1030	2100/2200	655	114/138/164	150/174/200	P1 340 x 1990/2090 P2 300 x 1987/2087
700(350x2) x 2000/2100	1180	2100/2200	755	114/138/164	150/174/200	P1 390 x 1990/2090 P2 350 x 1987/2087
800(400x2) x 2000/2100	1330	2100/2200	855	114/138/164	150/174/200	P1 440 x 1990/2090 P2 400 x 1987/2087
900(450x2) x 2000/2100	1480	2100/2200	955	114/138/164	150/174/200	P1 490 x 1990/2090 P2 450 x 1987/2087
1000(500x2) x 2000/2100	1630	2100/2200	1055	114/138/164	150/174/200	P1 540 x 1990/2090 P2 500 x 1987/2087
1100(550x2) x 2000/2100	1780	2100/2200	1155	114/138/164	150/174/200	P1 590 x 1990/2090 P2 550 x 1987/2087
1200(600x2) x 2000/2100	1930	2100/2200	1255	114/138/164	150/174/200	P1 640 x 1990/2090 P2 600 x 1987/2087

NOTE TECNICHE

A richiesta sono disponibili altri controtelai a misura speciale.
Le misure intermedie in L e H del controtelaio variano di 50 mm.

La luce nominale (L) è ridotta di circa 10 mm.

Per il controtelaio con struttura (ST) da 114 mm è consigliabile l'utilizzo di pannelli porta con spessore max (SP) di 40 mm, compresi eventuali cornici fermavetro.

Portata standard dei carrelli in dotazione: 120 kg.

TECHNICAL INFORMATION

Special systems can be produced on demand.

Intermediate sizes L and H are available in increments of 50 mm.

The doorway (L) is reduced by an approximate 10 mm.

Systems with 114 mm structure (ST) are suitable for doors up to 40 mm thick (SP), including panel arch top door.

Standard payload of the hanging kit supplied: 120 kg.